

BUILDING IS FULLY SPRINKLERED

630PR2600

Office of

Construction &

Facilities


Management


U.S. Department of Veterans Affairs


Project Number


Building Number


Drawing Number










































































GENERAL NOTES

LOCATIONS.

1. FIRE PROTECTION CONTRACTOR SHALL COORDINATE LOCATION OF ALL SPRINKLER HEADS AND PIPING WITH STRUCTURAL ELEMENTS, MECHANICAL, PLUMBING, ELECTRICAL EQUIPMENT, AND CEILING CONFIGURATION INDICATED ON DRAWINGS. WHERE NECESSARY SPRINKLER CONTRACTOR SHALL PROVIDE ADDITIONAL SPRINKLERS TO ASSURE REQUIRED DISCHARGE PATTERNS AROUND OBSTRUCTIONS AND DIFFERENT CEILING ELEVATIONS TO YIELD A PROPER DENSITY (gpm/sq.ft) FOR THE DESIGNED HAZARD.

2. ALL PIPING, FITTINGS, AND JOINTS IN SPRINKLER AND STANDPIPE SYSTEMS SHALL CONFORM TO NFPA 13 & 14, NON-METALLIC PIPE AND FITTINGS ARE UNACCEPTABLE.

3. ALL VALVES WILL BE READILY ACCESSIBLE FROM A SAFE HEIGHT ON A SIX FOOT LADDER AND TO BE CLEAR OF ALL OBSTRUCTIONS AND THEIR OPERATION SHALL NOT TO BE ENCUMBERED BY ANY DEVICE OR EQUIPMENT.

4. INSTALL ALL OVERHEAD HANGERS AND SUPPORTS PRIOR TO SPRAY FIREPROOFING OR DRYWALL CEILING.

5. SPRINKLER PIPING IS TO BE BRACED AND RESTRAINED (BRANCH LINES) IN ACCORDANCE WITH NFPA 13 FOR SEISMIC REQUIREMENTS.

6. SPRINKLER SYSTEM SHALL BE ZONED AS SHOWN ON DRAWINGS. 7. REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR SPRINKLER HEAD

8. THE SPACE ABOVE THE CEILING IS LIMITED AND THE INSTALLATION OF WORK WILL BE TIGHT. DUE TO THIS, IT IS IMPORTANT THAT THE TRADE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF THEIR WORK WITH THE CEILING SYSTEM HEIGHT AND CONSTRUCTION, THE STRUCTURAL SYSTEM, THE LIGHTING FIXTURES, THE SPRINKLER HEADS/MAINS, AND THE PLUMBING PIPES, ROUTE PIPING AS HIGH AS POSSIBLE. MAINTAIN PROPER SERVICE ACCESS CLEARANCES. ACCURATE SHOP

9. THESE DRAWINGS ARE DIAGRAMMATIC IN NATURE AND MAY NOT SHOW EXACT ROUTING OR ALL REQUIRED OFFSETS, ACCESSORIES, OR APPURTENANCES. CONTRACTOR SHALL PROVIDE AS REQUIRED TO INSTALL A COMPLETE AND COORDINATED JOB, INCLUDING ANY ADDITIONAL ITEMS REQUIRED TO MEET ACTUAL FIELD CONDITIONS AND ACTUAL EQUIPMENT SELECTED.

DRAWINGS SHALL BE SUBMITTED FOR APPROVAL, PRIOR TO FIELD INSTALLATION.

DESIGN CRITERIA

A. THE ENTIRE RENOVATION AREA SHALL BE HYDRAULICALLY DESIGNED IN ACCORDANCE WITH NFPA 13 AND STANDARDS FOR LIGHT HAZARD EXCEPT FOR MECHANICAL EQUIPMENT ROOMS, STORAGE AND ELECTRIC CLOSETS WHICH WILL BE ORDINARY HAZARD GROUP 1 AND CLEAN AND SOILED ROOMS WHICH WILL BE ORDINARY HAZARD GROUP 2.

B. THE FOLLOWING CRITERIA SHALL BE MEET:

1. ORDINARY HAZARD - DENSITY .15 GPM PER SQ. FT. OVER MOST HYDRAULICALLY REMOTE 1500 SQ. FT. MAXIMUM COVERAGE PER HEAD 130


2. EXACT LOCATION OF SPRINKLER HEADS IN FINISHED AREAS WITH SUSPENDED CEILINGS SHALL BE ON CENTER OF TILE AND AS INDICATED ON SPRINKLER CEILING PLANS. PIPING TO BE COORDINATED WITH OTHER TRADES.

3. DISCHARGE FROM EACH SPRINKLER HEAD SHALL NOT BE LESS THAN REQUIRED FOR AREA COVERED BY THIS HEAD. AREA COVERAGE PER HEAD SHALL BE DETERMINED IN ACCORDANCE WITH NFPA STANDARD NO. 13, PARAGRAPH 7-4.3.1.2.

4. MINIMUM PRESSURE AT SPRINKLER HEAD 7 PSI.

5. HYDRAULIC CALCULATIONS SHALL BE BROUGHT BACK TO CONNECTION TO WATER SUPPLY.


6. RESULT OF HYDRAULIC CALCULATIONS SHALL INDICATE MINIMUM 10 PSI PRESSURE SAFETY MARGIN, I.E. EXCESS OF PRESSURE AVAILABLE OVER PRESSURE REQUIRED.



SCALE: NTS

1. BRANCH SPRINKLER CONTROL VALVE SHALL BE BUTTERFLY VALVE WITH INDICATORS.

FIRE SPRINKLER ZONE CONTROL VALVE PIPING DETAIL B6







VA FORM 08-6231

